



# SYNO-Pierre®

## Product :

Syno-Pierre® is a decoration material, carried out according to the method of cement-glass composites (cementing matrix, armed with alkali-resistant glass fibre).

## Supports :

Syno-Pierre® is to be applied to breeze blocks, bricks, dry partitions, gypsum blocks or any other wall lining in new building or in restoration.

## Application :

It is very simple to apply Syno-Pierre® :

- With a comb, pre-paste the support and the stone with mortar-adhesive powder or paste, agreed by CSTB (Building Scientific and Technical Center).
- Apply Syno-Pierre® to the support and let the stone oscillate to ensure a better distribution of the adhesive.
- It is recommended to leave a joint from approximately 10 to 12 mm, which will make it possible to catch up with the differences in calibration which make all the charm of Syno-Pierre®
- Cuttings will be carried out with a grinding machine, equipped with a disc for materials.
- For electric cases, catches and other embeddings, it is advised to bore with a drill for concrete and then to cut out with a hole saw.

## Jointings :

To produce the joints of Syno-Pierre®, it is advised to use a traditional mixture (such as that usually employed by stone masons).

Such a mixture will be obtained from various sands (minimum granulometry 0,3 mm), lime or white cement.

Otherwise, it is possible to use a mural coating (minimum granulometry 0,3 mm).

- Fill the joint with your joint compound avoiding any overflow on the stone.
- Let it dry 3 to 4 hours, according to the temperature and hygroscoy of the room.
- Once dry, the joint stays friable so that you can eliminate the surplus of paste with a trowel.
- Brush joint and possible overflows, with a scrubbing brush. Never use sponges, neither dry nor wet : it would cause irreversible efflorescences.

## Tools :

Trowel, flat trowel for joint, masonry stencil, scrubbing brush.

Other products of the range :

- Syno-Bric : In the shape of briquette lintels.
- Syno-Bois : with the appearance of old beams in oak.
- Syno-Bric and Syno-Bois make it possible to create half-timberings on new walls or to renovate existing half-timberings.

**Easy to apply :  
just like tiling**



## Syno-Mat SARL

Z.I. La Vergnasse - 33660 Saint-Seurin-Sur L'Isle - FRANCE

Tél. 00 33 (0) 5 57 49 66 90 - Fax : 00 33 (0) 5 57 49 66 96 -

[www.syno-mat.fr](http://www.syno-mat.fr)